# Natur-Tec<sup>™</sup>

Sustainable Biobased Materials

# 2016 NZWBC The Macro Cost of Micro Contamination

**Compostable Plastics v Traditional Plastics** 

# Agenda



- Introduction to Natur-Tec®
- Why are we here?
- Compostable plastics and what to look for?
- What are traditional plastics?
- Plastic contamination in soils
- Presentation takeaways

# Introduction

**Natur-Tec** is a specialty compounder and formulator of biobased and compostable bioplastics.

- Assist with LEED certification efforts
- Meets ASTM D6400 and FN13432 standard specifications for compostable plastics
- Made from renewable content as per ASTM D6866

Available product portfolio comprises of:

- Natur-Bag<sup>®</sup> compostable trash bags and bin liners
- Natur-Ware<sup>®</sup> biobased and compostable cutlery



Natur-Tec

- **Natur-Tec** is a proud partner of **Ei**, a national non-profit
- Member of Sustainable Materials ACTION Team





Natur-Tec™



#### Rubber, leather Other 4.3% & textiles Yard Food waste 11.2% Food waste trimmings 14.5% Other 3.4% 13.5% 21.1% Wood 6.3% Rubber, leather Paper & paperboard Wood & textiles 14.8% 8.2% 8.7% Paper & paperboard Yard trimmings 27.4% 8.7% Plastics Plastics 12.7% 17.6% Metals Glass 9.0% Glass Metals 5.1% 4.6% 8.9%

Total MSW Generation (by material):

2012 - 251 Million Tons (before recycling and composting)

Data and Charts: EPA "Municipal Solid Waste Generation, Recycling, and Disposal in the United States: Facts and Figures for 2012"

#### **Total MSW Discards (by material):** 2012 - 164 Million Tons (after recycling and composting)

# **EPA Food Recovery Hierarchy**

#### **Food Recovery Hierarchy** Most Preferred Source Reduction Reduce the volume of surplus food generated **Feed Hungry People** Donate extra food to food banks, soup kitchens and shelters **Feed Animals** Divert food scraps to animal feed **Industrial Uses** Provide waste oils for rendering and fuel conversion and food scraps for digestion to recover energy Composting Create a nutrient-rich soil amendment Landfill/ Incineration Least Preferred Last resort to disposal

Natur-Tec

# **Drivers for Organic Recycling**



Natur-Tec

- Organic waste in landfills decomposes anaerobically into Methane, which is <u>23 times</u> more dangerous than CO<sub>2</sub> as a Green House Gas (GHG)
- Improved soil health (reduce fertilization requirements)
- Increased water retention (compost retains 3x the amount of water as untreated soil).
- Filters water run off 60-95% better than standard, untreated soil
- Increased crop yield

### **Integrated Zero Waste Solutions**



www.natur-tec.com | www.naturbag.com

#### **Zero Waste Program** Considerations and Enablers


- Know and understand local MSW policy
- Know and understand existing hauling, concessionary contracts, lease agreements, etc.
- Engage diversion stakeholders (haulers, processors, etc.)
- Establish baseline metrics with on-going waste audits.
- Control product supply: compostable, reuse, and recycle
- Readily available sorting stations and effective signage
- On-going education and engagement







#### ©2016 NTIC



**Fragmentation** – first step in the biodegradation process, in which organic matter is broken down into microscopic fragments

**Biodegradability** – *complete* microbial assimilation of the fragmented product as a food source by the soil microorganisms.

**Compostability** – complete assimilation *within* <u>180 days</u> in an industrial <u>compost</u> <u>environment</u>.

# End of Life ASTM Standards

# ASTM D6400

- Specification for Compostable Plastics
- For plastic films and solid plastic products

# ASTM D6868

- *Specification* for *Compostable Plastic* used on Paper and other Compostable Substrates
- For packaging and food service items, made of plastic coated paper, board, and other fibers



Natur-Tec"




Similar to European, Japanese, and ISO Standards



#### **AEROBIC** (composting environment)

Glucose/C-bioplastic + 6 O<sub>2</sub>

 $6 CO_2$  +  $6 H_2O$ ;  $\Delta G^{0'} = -686$  kcal/mol



## **Specification for Compostable Plastics**

## **ASTM D6400 Specifies Three Criteria**

- 1. Disintegration (Section 6.2)
  - Less than 10% of test material remains on 2mm sieve
  - Controlled compost conditions at thermophilic conditions (135°F / 58°C) as defined in ASTM D5338 & ISO 16929 test methods
  - Time: 12 weeks or less (84 days)

#### 2. Mineralization / Inherent Biodegradation (Section 6.3)

- 90% Conversion to carbon dioxide, water & biomass via microbial assimilation
- **ASTM D5338** defines test method used
- Time: 180 days or less (the same rate as natural materials leaves, paper, grass, food scraps)

#### 3. Safety (Section 6.4)

- No impacts on plant growth, using OECD Guide 208
- Regulated (heavy) metals less than 50% of EPA prescribed threshold







The Biodegradable Products Institute (BPI), provides an independent certification program for products that meet all requirements of the ASTM D6400 standard


Natur-Tec

- Uses independent approved labs and reviewers
- Not based only upon manufacturer's claims



"The Proof is in the Label"

# Additive Technologies



Natur-Tec™

# **Environmental Impact**





Determining the Amount of Plastic and Compostable Plastic in Compost "Overs"

Natur *→*Tec<sup>™</sup>



Study conducted on behalf of the Biodegradable Products Institute

October 2012

INTEGRATED WASTE MANAGEMENT CONSULTING, LLC NEVADA CITY, CALIFORNIA



# What are Plastics?





**"Plastic** is a material consisting of any of a wide range of <u>synthetic</u> or semisynthetic <u>organics</u> that are <u>malleable</u> and can be <u>molded</u> into solid objects of diverse shapes. Plastics are typically <u>organic polymers</u> of high <u>molecular mass</u>, but they often contain other substances. They are usually synthetic, most commonly derived from <u>petrochemicals</u>, but many are partially natural"

- Wikipedia

# A Disposable Culture Emerges









#### Throwaway Living DISPOSABLE ITEMS CUT DOWN HOUSEHOLD CHORES



Natur-Tec™






# Compostable Plastics vs. Polyethylene

Microbes utilize carbon substrates to extract chemical energy to support life processes.

Natur-Tec"

- Certain polyesters (like Eco-Flex and PLA) have a chemical structure of –O-CO-. These are "weaker" molecular bonds and are capable of being assimilated by soil microorganisms.
- Polyethylene (traditional plastic bags) and other polyolefins have a C-C chemical structure. These are "stronger" bonds and are not capable of being assimilated by soil microorganisms.



# Wood's End and Eco-Cycle Study

New Opportunities in Recycling and Product Manufacture Eliminate the Environmental Hazards Inherent in the Composting of Plastic-Coated Paper Products

> <sup>1</sup>Woods End Laboratories, Inc., Mt. Vernon, ME <sup>2</sup>Eco-Cycle, Inc., Boulder, CO



nd" Workd

April 2011



Natur-Tec"

"....there has been growing concern in the scientific community about the increased accumulation of plastic fragments in the environment, their absorption of persistent organic pollutants (POPs), their ingestion by organisms, and the human health and environmental consequences that may result"

## Wood's End and Eco-Cycle Study



Natur-Tec"

RELEASED FROM ALL PLASTIC-COATED PAPER PRODUCTS SUCH AS THIS PAPER ORANGE JUICE CARTON, SHOWN BEFORE AND AFTER TESTING.

"This study showed conclusively that micro-plastic fragments <u>were shred from all</u> <u>plastic coated samples</u>, whether single or double-coated. This means any plasticcoated paper product, even those that are partially screened out during the composting process, is contaminating the finished compost with plastics particles."

- Plastic food service packaging made from traditional plastic is difficult to recycle, look to compost certified compostable food service packaging when possible.
- When using compostable food service plastic wares ensure they are in compliance to ASTM D6400 / ASTM D6868 certified compostable by the BPI
- Products made from traditional plastics do not fully biodegrade and should not be sent to a compost facility



Natur-Tec

# Thank You!



#### Rick Lombardo

Director, Business and Market Development Phone: 517.230.5995 Email: <u>rlombardo@ntic.com</u>



